



K I N T E K F U R N A C E

D e n t a l F u r n a c e

C o n t a c t u s f o r H i g h T e m p e r a t u r e F u r n a c e s ,

K I N T E K F U R N A C E

> > >

CVD / PECVD



: K T - D V 1 0



K i n T e k : .

	200 / (392 ° F /)
	1200 (2283 ° F)
	2
	1 - 101%
	100 - 120V 50 / 60HZ 230V 50 / 60HZ
	14.5 @110V 7.0 @230V
	1500W
	H27cm x W36cm x D53cm
	9cm (3.5 ")
	20Kg
	23.5Kg

: K T - D S 1 0



:
9
, 1530 °C , SiC
!

	200 / (392 ° F /)
	1530
	2
	100 - 120V 50 / 60HZ 230V 50 / 60HZ
	14.5 @110V 7.0 @230V
	1500W
	H27cm x W36cm x D56cm
	9cm (3.5 ")
	20Kg
	25.5Kg

: K T - D P 1 0



: ± 1 ° C

1 2 0 0 ° C ,

!

	2 0 0 / (3 9 2 ° F /)
	1 2 0 0 (2 2 8 3 ° F)
	2
	1 - 1 0 1 %
	1 0 0 - 1 2 0 V 5 0 / 6 0 H Z 2 3 0 V 5 0 / 6 0 H Z
	1 4 . 5 @ 1 1 0 V 7 . 0 @ 2 3 0 V
	1 5 0 0 W
	H 2 7 c m x W 3 6 c m x D 7 0 c m
	9 c m (3 . 5 ")
	2 3 K g
	2 6 . 5 K g



K i n t e k F u r n a c e

W h a t s A p p

Image not found